



# CM 202 THINNER

Product Code : CM THN 202

## Product Descriptions

CM 202 Thinner is a general purpose thinner that can be used as a superior cleanser and to improve paint consistency.

## Recommended Uses

Recommended for thinning solvent-based paints or varnishes. Superior cleaner and degreaser for final cleanup of wood and metal surfaces. Cleans brushes and equipment immediately after use. Can be used on most plastic surfaces. Do not use to thin water-based paints, latex coatings, lacquer or shellac. Do not use as a cleaner for linoleum or tile floors or other solvent-sensitive surfaces.

## Product Characteristics

### Composition:

Pigment	
Binder	
Solvent	
Volume Solid	

### Properties :

Colour Range	Clear Liquid
Texture	None.
Shelf life/Storage	Use within 12 months of delivery.Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner. Up to 2 years storage life at 25'c to 30'c.
Standard Packing Size	300ml / 600ml/ 3Litres/ 15 Litres

### Typical Performance Data (approx.):

Coverage	
Recommended no. of coats	
Drying time (Application Temperature 25'c to 30'c)	Touch Dry: Hard Dry :
Recoating Interval	

## **Directions for use**

### **Application:**

Capable to thin :

- ❖ *CM 5500 Royal High Gloss Paint*
- ❖ *CM 9900 Premium High Gloss Paint*
- ❖ *CM Acrylic Roof Coating*
- ❖ *CM 1P Floor Covering Finish*
- ❖ *CM 2P EP Heavy-Duty Coating*
- ❖ *CM EX9000 Heat Resisting Aluminium 200'c*
- ❖ *CM EX9000 Heat Resisting Aluminium 600'c*
- ❖ *CM EX9000 Micaceous Iron Oxide*
- ❖ *CM EX9000 Roadline Paint*
- ❖ *CM EX9000 White Undercoat*
- ❖ *CM EX9000 Aluminium Paint*
- ❖ *CM EX9000 Epoxy Primer*
- ❖ *CM EX9000 Conventional Metal Primer*
- ❖ *CM 9900 QD White Undercoat*
- ❖ *CM Industrial Primers*
- ❖ *CM Timber Colour Finish*
- ❖ *CM Timber Stain*
- ❖ *CM U-Colux Automotive Finish*
- ❖ *CM Zinc Chromate Primer*

### **Health, Safety and Environmental information:**

It is advisable to wear eye protection when applying paint.

In case of contact with eye, immediately flush eyes with plenty of water for at least 15 minutes and seek medical advice.

In case of contact with skin, immediately flush skin with plenty of water and soap while removing contaminated clothing and shoes and seek for medical advice.

Keep containers tightly closed and out of reach from children. Paints should always be stored in a cool place.

Containers that are opened should be properly released and keep upright to prevent leakage.

When transporting paint, care must be taken. Always keep container in a secure upright position.

Wastes and empty containers should be treated and disposed of in accordance with national and local regulations.

## **Disclaimer**

The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.

This Data Sheet supersedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of CM Paints (M) Sdn. Bhd. . The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.