

CM 9000 QD WHITE UNDERCOAT

Product Code : CM QDW

Product Descriptions

CM 9000 QD White Undercoat is a solvent based air dried alkyd undercoat. It is specially designed to meet economical needs. It has good hiding and build and can be served as a good foundation for *CM ROYAL 5500 HIGH GLOSS* & *CM 9900 PREMIUM HIGH GLOSS*.

Recommended Uses

Highly recommended for use on primed metal, woodwork and previously painted surfaces prior to *painting CM 5500 HIGH GLOSS* & *CM 9900 Premium High Gloss*.

Product Characteristics

Composition:

Pigment	Titanium Dioxide and Mineral Extenders	
Binder	Modified Long Oil Alkyd	
Solvent	White Spirit	
Volume Solid	65%±	

Properties :

Colour Range	White
Texture	Matt
Shelf life/Storage	Use within 24 months of delivery. Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner.
Standard Packing Size	7Litre & 18 Litres *Other Sizes by special arrangement.

Typical Performance Data (approx.):

Coverage	Approximately 10-12 m ² per litre		
	*Actual coverage is dependent on substrate condition.		
	*These figures do not include wastage.		
Recommended no. of	1 coat		
coats			
Drying time	Touch Dry: 30 Minutes		
(Application	Hard Dry : \geq 6 Hours		
Temperature 25'c to			
30'c)			
Recoating Interval	Overnight		

Directions for use

Preparation:

Wood

1. Wood must be dry and free from dirt, grease and free from other contaminants. Abrade the surfaces with sandpaper if necessary.

Metal

1. Metal surface must be dry and free from dirt, grease and free from other contaminants. Ferrous substrate should be sanded or wire-brushed to remove mill scales and rust. Clean off and dry.

Application:

- 1) Brush/Roller : The paint is ready to use after thorough stirring. Thin 5% *CM 202 thinner* by volume if necessary.
- 2) Compressed Air Spray: Thin 10-20% CM 202 Thinner by volume as necessary.
- 3) Airless Spray: The paint is ready to use after thorough stirring Thin 5% *CM 202 thinner* by volume if necessary.

Recommended Paint System

Wood Surface:

Sequence	Product Name	No. of Coats
Primer	CM EX9000 Aluminium Wood	1
	Primer	
Undercoat	CM 9000 QD White Undercoat	1
Finish	CM 9900 Premium High Gloss	2

Metal Surface

Sequence	Product Name	No. of Coats
Primer	CM Industrial Primer/	1-2
	CM Zinc Chromate Primer	
Undercoat	CM 9000 QD White Undercoat	1
Finish	CM 9900 Premium High Gloss	2

Health, Safety and Environmental information:

It is advisable to wear eye protection when applying paint.

In case of contact with eye, immediately flush eyes with plenty of water for at least 15 minutes and seek medical advice.

In case of contact with skin, immediately flush skin with plenty of water and soap while removing contaminated clothing and shoes and seek for medical advice.

Keep containers tightly closed and out of reach from children. Paints should always be stored in a cool place. Containers that are opened should be properly released and keep upright to prevent leakage.

When transporting paint, care must be taken. Always keep container in a secure upright position.

Wastes and empty containers should be treated and disposed of in accordance with national and local regulations.

Disclaimer

The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.

This Data Sheet supersedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of CM Paints (M) Sdn. Bhd. . The user must also satisfy himself of the suitability of the product in circumstances other that those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.